

PETROVAST

Steam hose for heavy duty industrial cleaning and circulation of saturated and superheated steam in heating systems. Inner hose from 10 to 51 mm.



Technical information:

Inner hose: black, smooth EPDM.

Cover hose: black, fabric impression EPDM.

Reinforcement: brasscoated steel, braided.

Temperature range: water: -40°C to +120°C, P_{work}= 60 bar.

saturated steam: +210°C, P_{work}= 18 bar.

superheated steam: +230°C, P_{work}= 18 bar .

Applications: for heavy duty industrial cleaning and circulation of saturated and superheated steam in heating systems. Used in the petrochemical, building, shipyard, and chemical industry.

Advantages: multipurpose hose. Highly flexible. Very high temperature resistance. Chemical resistant.

Producer: Trelleborg (France)

Hose length: see in the table

PETROVAST						
Code	Øin., mm	Øout., mm	Working pressure, bar	Bursting pressure, bar	Weight, kg/m	Coil length, m
STEAM-010-18-TRE	10	22	18	180	0.41	20-40
STEAM-013-18-TRE	13	25	18	180	0.48	20-40
STEAM-016-18-TRE	16	30	18	180	0.67	20-40
STEAM-019-18-TRE	19	33	18	180	0.77	20-40-60
STEAM-025-18-TRE	25	40	18	180	1.06	20-40-60
STEAM-032-18-TRE	32	48	18	180	1.38	20-40
STEAM-038-18-TRE	38	54	18	180	1.60	20
STEAM-051-18-TRE	51	69	18	180	2.54	20

HIDROBALT

Quality and reliability since 1995..