

605AA

Fuel-oil S&D 10 bar exceed SAE 100R4 SAE J2006/R2 - ISO 13363/2/A+B. Inner hose from 19 to 203 mm.



Technical information:

Inner hose: black conductive NBR.

Cover hose: black CR - abrasion, ozone and hydrocarbon resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Temperature range: -30°C to +80°C.

Applications: fuel and oil suction and delivery. Specially designed for tank truck and general industrial applications. Also suitable for marine wet exhaust and bilge pump connection.

Producer: Alfagomma (Italy)

Hose length: see in the table

605AA								
Code	Øin., mm	Øout., mm	Working pressure, bar	Bursting pressure, bar	Vakuum, %	Bending radius, mm	Weight, kg/m	Coil length, m
FUEL-019-10-ALF	19	29	10	30	100	76	0.61	30.5
FUEL-025-10-ALF	25	35	10	30	100	100	0.76	30.5
FUEL-032-10-ALF	32	42	10	30	100	128	0.90	30.5
	35	45	10	30	100	140	0.98	30.5
FUEL-038-10-ALF	38	48	10	30	100	152	1.05	30.5
FUEL-051-10-ALF	51	61	10	30	100	204	1.35	30.5
FUEL-063-10-ALF	63	75	10	30	90	252	2.11	30.5
FUEL-076-10-ALF	76	88	10	30	90	304	2.52	30.5
FUEL-102-10-ALF	102	116	10	30	90	408	3.50	30.5
FUEL-110-10-ALF	110	124	10	30	90	440	4.24	30.5
FUEL-127-10-ALF	127	145	10	30	80	508	5.93	30.5
FUEL-152-10-ALF	152	170	10	25	80	608	7.36	30.5
FUEL-203-10-ALF	203	225	10	25	70	812	11.70	30.5

If you can't find exact diameter – you need to ask