

APOLLO SE

Suction PVC hose for water. Inner hose from 25 to 300 mm.



Technical information:

Inner hose: inside surface smooth, blue PVC.

Cover hose: light blue with an extruded red stripe, corrugation PVC.

Reinforcement: hose reinforced with an anti-shock rigid Pvc spiral.

Temperature range: -25°C to +60°C.

Applications: excellent for suction in general, particularly suitable to be used on tank trucks thanks to its physical- mechanical features.

Producer: IPL (Italy)

Hose length: see in the table

| APOLLO SE | | | | | | | | |
|---------------|-------------|--------------|-----------------------------|------------------------------|--------------|--------------------------|-----------------|----------------------|
| Code | Øin., mm | Øout., mm | Working pressure, bar | Bursting pressure, bar | Vakuum, % | Bending radius, mm | Weight, kg/m | Coil length, m |
| APOLLO-SE-032 | 32 | 4.3 | 6 | 18 | 100 | 130 | 0.59 | 50 |
| APOLLO-SE-038 | 38 | 4.4 | 5 | 15 | 100 | 155 | 0.69 | 50 |
| APOLLO-SE-050 | 50 | 4.9 | 4 | 12 | 100 | 200 | 0.98 | 50 |
| APOLLO-SE-063 | 63 | 5.5 | 4 | 12 | 90 | 260 | 1.39 | 50 |
| APOLLO-SE-076 | 76 | 6.2 | 3 | 9 | 90 | 310 | 1.70 | 50 |
| APOLLO-SE-080 | 80 | 6.0 | 3 | 9 | 90 | 320 | 1.89 | 50 |
| APOLLO-SE-090 | 90 | 6.3 | 3 | 9 | 90 | 360 | 2.20 | 30 |
| APOLLO-SE-100 | 100 | 7.7 | 3 | 9 | 85 | 410 | 2.70 | 30 |
| APOLLO-SE-102 | 102 | 7.7 | 3 | 9 | 85 | 410 | 2.75 | 30 |
| APOLLO-SE-110 | 110 | 7.8 | 3 | 9 | 85 | 450 | 3.00 | 30 |
| APOLLO-SE-127 | 127 | 8.1 | 2.5 | 7.5 | 80 | 510 | 3.60 | 30 |
| APOLLO-SE-152 | 152 | 8.9 | 2 | 6 | 80 | 610 | 5.28 | 20 |
| APOLLO-SE-160 | 160 | 9.3 | 2 | 6 | 70 | 660 | 5.67 | 20 |
| APOLLO-SE-200 | 200 | 12.1 | 1.5 | 4.5 | 70 | 850 | 9.90 | 10 |
| APOLLO-SE-250 | 250 | 13.2 | 1.0 | 3 | 65 | 1500 | 14.0 | 10 |
| APOLLO-SE-300 | 300 | 14.2 | 0.8 | 2.4 | 60 | 1800 | 17.5 | 10 |

If you can't find exact diameter – you need to ask