

EOLO PU FOOD

Suction and transportation of abrasive media such as powders, pellets, granulates, fibres, can be used for dedusting and industrial cleanings.
Inner hose from 20 to 300 mm.



Technical information:

Inner hose: smooth, ether based polyurethane, food grade.

Cover hose: corrugated, ether based polyurethane, food grade.

Reinforcement: an anti-shock rigid, PVC spiral, food grade.

Temperature range: -40°C to +80°C.

Applications: light suction of abrasive food.

Producer: IPL (Italy)

Hose length: see in the table

EOLO PU FOOD						
Code	Øin., mm	Max wall thickness, mm	Vakuum, %	Bending radius, mm	Weight, kg/m	Coil length, m
EOLO-PU-FOOD-020	20	2.5	25	25	0,11	20
EOLO-PU-FOOD-025	25	2.6	25	30	0.15	20
EOLO-PU-FOOD-032	32	2.6	20	35	0.18	20
EOLO-PU-FOOD-038	38	2.8	20	50	0.22	20
EOLO-PU-FOOD-045	45	2.9	20	65	0.27	20
EOLO-PU-FOOD-050	51	3.2	20	70	0.32	20
EOLO-PU-FOOD-063	63	3.6	16	80	0.51	20
EOLO-PU-FOOD-070	70	3.9	16	95	0.56	30
EOLO-PU-FOOD-076	76	3.9	16	100	0.60	30
EOLO-PU-FOOD-102	102	4.4	13	140	0.83	30
EOLO-PU-FOOD-110	110	4.7	12	150	0.95	30
EOLO-PU-FOOD-120	120	5.0	10	160	1.10	30
EOLO-PU-FOOD-127	127	5.0	10	170	1.15	30
EOLO-PU-FOOD-140	140	5.3	9	180	1.43	20
EOLO-PU-FOOD-150	151	5.3	8	200	1.50	20
EOLO-PU-FOOD-200	200	6.7	4	260	2.30	20
EOLO-PU-FOOD-300	300	7.7	3	350	4.10	10

If you can't find exact diameter – you need to ask

HIDROBALT

Quality and reliability since 1995..